



Sigen Hybrid Inverter

Three Phase

- Battery ready, future proof
- Up to 4 MPP. trackers
- IP66 protection rating

Sigen Hybrid Inverter 5.0-25.0 kW Three Phase

Sigen Hybrid	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	Units	
DC Input											
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	W	
Max. DC input voltage					1100					V	
Nominal DC input voltage					600					V	
Start-up voltage					180					V	
MPPT voltage range					160 ~ 1000						V
Number of MPP. trackers	2			3			4				
Number of PV strings per MPPT					1						
Max. input current per MPPT					16					A	
Max. short-circuit current per MPPT					20					A	
AC Output (on-grid)											
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	W	
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	VA	
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	A	
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	A	
Nominal output voltage					380 / 400						V
Nominal grid frequency					50 / 60						Hz
Power factor					0.8 leading ~ 0.8 lagging						
Total current harmonic distortion					THDi < 2%						
Efficiency											
Max. efficiency	98.1%	98.2%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%		
European efficiency	96.1%	96.6%	97.1%	97.5%	97.7%	97.9%	97.9%	97.9%	98.0%		
Additional Features											
Compatible battery module					SigenStor BAT 5.0 / 8.0						
Number of modules per controller					1 ~ 6						pcs
Battery module voltage range					600 ~ 900						V
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	W	
Nominal output voltage					380 / 400						V
Protection											
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ¹ , AC overcurrent/overvoltage/short-circuit protection. Type II DC/AC surge protection, Anti-islanding protection										
General Data											
Dimensions (W / H / D)					700 / 300 / 283						mm
Weight					36						kg
Storage temperature range					-40 ~ 70						°C
Operating temperature range					-30 ~ 60						°C
Relative humidity range					0% ~ 95%						
Max. operating altitude					4000						m
Cooling					Smart air cooling						
Ingress protection rating					IP66						
Installation method					Wall-mounted						
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)										
Standard Compliance											
Standard ²	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2										

1. This is an optional feature only supported in certain models, please contact Sigenergy for more information.
2. For all standards refer to the certificates category in the Sigenergy website.