

Sigen Power Sensor

- WiFi halow remote communication functionality (with Sigen Sensor Sub1G Kit)
- Efficient and stable data transmission up to 200m (with Sigen Sensor Sub1G Kit)
- 1% high-accuracy power detection for precise control
- LCD real-time info display, easy to operate and check
- Integrate smoothly with Sigenenergy devices, no need for setup
- Top class 100 A direct connection in power sensor with built-in CT
- 100 ms data refresh rate, instantaneous data feed

Sigen Sensor Sub1G Kit



Sigen Power Sensor



Sigen Power Sensor

Sigen Sensor ¹	SP-DH	SP-CT120-DH	TP-DH	TP-CT120-DH	Units
Power Supply					
Grid connection type	1P2W		3P3W/3P4W		
AC input voltage range	176 ~ 276		173 ~ 480		Vac
Nominal AC frequency			50 / 60		Hz
Max. operating current	100	-	100	-	A
Measurement Accuracy					
Voltage accuracy			0.5%		
Current accuracy			0.5%		
Power accuracy			1%		
Frequency accuracy			0.2%		
Communication					
Interface			RS485		
Baud rate			9600		bps
Protocol			Modbus RTU		
General Data					
Dimensions (W / H / D)	36 / 100 / 63	18 / 118 / 64	72 / 100 / 66	72 / 94.5 / 65	mm
Weight	0.20	0.07	0.32	0.20	kg
Storage temperature range			-40 ~ 70		°C
Operating temperature range			-25 ~ 60		°C
Relative humidity range			0% ~ 90%		
Ingress protection rating			IP20		
Installation method			DIN Rail 35 mm		
CT Accessory					
Number of CT	-	1	-	3	pcs
Cable length of CT	-	1	-	1	m
Inner diameter of CT	-	16	-	16	mm
Weight of CT	-	0.09	-	0.09	kg
Max. operating current of CT	-	120	-	120	A
Standard Compliance					
Standard	EN 61010-1:2010, EN 61010-2-030:2010				

	Sigen Sensor SubIG Kit	Units
Working mode	AP(master device), STA(slave device)	
Communication method	RS485 / wireless communication	
Protocol	IEEE 802.11ah	
Operating voltage	85 ~ 277	Vac
Power consumption	2	W
Operating temperature range	-25 ~ 55	°C
Dimensions (W / H / D)	18 / 118 / 66	mm
Wireless frequency	868	MHz
Wireless transmission distance ²	≤ 200	m
Installation method	DIN Rail 35 mm	

1. For more models refer to the Sigenenergy website.

2. Lab tests have shown a maximum horizontal range of up to 200 metres in open spaces, with shorter communication distances when walls are in the way.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.